

**AN IMAGE CAPTURE DEVICE, A METHOD OF CAPTURING IMAGES, AN
IMAGE PRODUCING DEVICE AND A METHOD OF PRODUCING IMAGES**

Cross Reference to Related Application

5 This application claims priority to Japanese Patent
Application No. JP-2000-319773, and the disclosure of
that application is incorporated herein by reference to
the extent permitted by law.

10 **Background of the Invention**

1. Field of the Invention

 The present invention relates to an image capture
device for capturing images of an object, a method of
15 capturing images thereof, an image producing device for
producing images and a method thereof.

2. Description of the Related Art

 Generally, recording of graphics information has
20 been directed mostly to recording of planar 2-dimensional
graphics information, however, recently, a technology for
recording a solid (stereoscopic) image such as a
holographic stereogram is being realized.

 The holographic stereogram is produced, for example,
25 in such a manner that a plurality of images of an object
are captured sequentially from different viewing points
as its original images, then they are sequentially
exposed to be recorded as element holograms in a strip or
dot patterns on a single hologram recording medium. When
30 this holographic stereogram is viewed by an observer with
his/her one eye from a given position, a set of multiple

pieces of graphic information recorded as part of each
element hologram are recognized as a 2-dimensional image,
while on the other hand, when viewed by the observer with
one eye from another position different from the above-
5 mentioned given position, a set of multiple pieces of
graphic information recorded as another part of the each
element hologram are recognized as another 2-dimensional
image. Therefore, when the observer views the holographic
stereogram with his/her both eyes, its exposed and
10 recorded image is recognized as a 3-dimensional image
because of a parallax between the both eyes.

As related applications utilizing such holographic
stereogram, there are printer systems that combine an
image capturing device for capturing images of an object
15 and forming a string of parallax image thereof with a
printing device for generating a holographic stereogram
and outputting as a printed matter, for example, as
disclosed in "Instant holographic portrait printing
system" by Akira Shirakura, Nobuhiro Kihara and Shigeyuki
20 Baba, Proceedings of SPIE, Vol. 3293, pp.246-253, Jan.
1998, "High-speed hologram portrait print system" by
Kihara, Shirakura, Baba, 3-D Image Conference 1998, July,
1998, and the like. These printing systems can provide a
set of services from an image capturing of an object to
25 printing of its holographic images at the same service
spot.

Summary of the Invention

When a parallax image string is obtained by shooting
30 its images as done in the printer systems described above,
it should be noted that there exist various parameters to

be considered such as an image shooting angle, a shooting distance indicating a positional relation between an object and a viewing (shooting) point, a length of translation motion of an image capturing device, and a pitch of shooting. Further, when producing a holographic stereogram and outputting it as a printed matter, there are various parameters also to be considered in its printing device such as at what viewing angle and at what exposure pitch its holographic stereogram should be exposed and recorded, and so on.

Here, also it should be noted that in a case of producing a printed matter such as the holographic stereogram using the parallax image string which is obtained with the image-capturing device, it becomes necessary to ensure for various parameters in the image capturing device and those in the printing device to be matched and coordinated therebetween. If there is any mismatching therebetween, a proper and correct solid (stereoscopic) image cannot be obtained.

The parallax image string can also be produced as computer graphics images created such as CG (Computer Graphics). Even in such a case where a printed matter, for example, of a holographic stereogram is produced using the parallax image string created by CG or the like, it is essential in order to be able to obtain a proper and correct stereoscopic image that various parameters at the time of image shooting and at the time of printing in its printer are matched and coordinated therebetween.

For example, in a white light reproduced holographic stereogram, there occurs such a phenomenon that a distortion and/or blurring in a holographic stereogram